



## Safety Data Sheet

Copyright, 2021, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	34-3587-2	<b>Version number:</b>	2.00
<b>Issue Date:</b>	10/11/2021	<b>Supersedes date:</b>	03/10/2018

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

### IDENTIFICATION:

#### 1.1. Product identifier

3M™ Platinum Select Filler PNs 31128, 31131

#### Product Identification Numbers

60-4550-8436-2      60-4550-8458-6

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Automotive., Body Filler

#### 1.3. Supplier's details

<b>Address:</b>	3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113
<b>Telephone:</b>	136 136
<b>E Mail:</b>	productinfo.au@mmm.com
<b>Website:</b>	www.3m.com.au

#### 1.4. Emergency telephone number

**Company Emergency Hotline:** EMERGENCY: 1800 097 146 (Australia only)

**This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the SDSs for components of this product are:**

34-0251-8, 29-5993-0

One or more components of this KIT is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

### TRANSPORT INFORMATION

The Dangerous Goods Classification for the complete Kit is provided below.

**UN No.:** UN3269

**Proper shipping name:** POLYESTER RESIN KIT

**Class/Division:** 3  
**Packing Group:** III  
**Marine Pollutant:** Not applicable.

**Hazchem Code:** •2YE  
**IERG:** 15

**Australian Dangerous Goods Code (ADG) - Road/Rail Transport**  
**Special Instructions:** Limited quantity may apply

**International Air Transport Association (IATA)- Air Transport**  
**Special Instructions:** Forbidden, package size exceeds IATA quantity limitations

**International Maritime Dangerous Goods Code (IMDG)- Marine Transport**  
**Special Instructions:** Limited quantity may apply

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

**3M Australia SDSs are available at [www.3m.com.au](http://www.3m.com.au)**



## Safety Data Sheet

Copyright, 2023, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	34-0251-8	<b>Version number:</b>	2.01
<b>Issue Date:</b>	04/07/2023	<b>Supersedes date:</b>	10/11/2021

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Platinum Select Filler PN's 31128, 31130, 31131, 31132, 35863

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Automotive, Body filler

For Industrial or Professional use only.

#### 1.3. Supplier's details

<b>Address:</b>	3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113
<b>Telephone:</b>	136 136
<b>E Mail:</b>	productinfo.au@mmm.com
<b>Website:</b>	www.3m.com.au

#### 1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

### SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

#### 2.1. Classification of the substance or mixture

Flammable liquid: Category 3.

Serious Eye Damage/Irritation: Category 2.

Carcinogenicity: Category 1A.

Specific Target Organ Toxicity (single exposure): Category 1.

Specific Target Organ Toxicity (repeated exposure): Category 1.

#### 2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product

label.

## Signal word

Danger

## Symbols

Flame | Exclamation mark | Health Hazard |

## Pictograms



## Hazard statements

H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H350	May cause cancer.
H370	Causes damage to organs: liver   sensory organs.
H372	Causes damage to organs through prolonged or repeated exposure: respiratory system   sensory organs.
H373	May cause damage to organs through prolonged or repeated exposure: liver.

## Precautionary statements

### General:

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.

### Prevention:

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P280F	Wear respiratory protection.

### Response:

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P314	Get medical advice/attention if you feel unwell.
P337 + P313	IF eye irritation persists: Get medical advice/attention.

P370 + P378

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

**Storage:**

P403 + P235  
P405

Store in a well-ventilated place. Keep cool.  
Store locked up.

**Disposal:**

P501

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**2.3. Other assigned/identified product hazards**

None known.

**2.4. Other hazards which do not result in classification**

May be harmful if swallowed.

Causes mild skin irritation.

May be harmful if inhaled.

Harmful to aquatic life with long lasting effects.

**SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
Talc	14807-96-6	15 - 40
Resin Polymer	Trade Secret	15 - 40
Styrene	100-42-5	< 20
Magnesium Carbonate	546-93-0	5 - 10
Inert Filler	Trade Secret	5 - 10
Polyester Polymer	Trade Secret	5 - 10
Titanium dioxide	13463-67-7	1 - 5
Limestone	1317-65-3	1 - 5
Synthetic Crystalline-Free Silica Gel	112926-00-8	1 - 5
Chlorite-group minerals	1318-59-8	< 1.5
Dolomite	16389-88-1	< 1.5
Ethylbenzene	100-41-4	< 0.5
Quartz	14808-60-7	< 0.5
Cobalt bis(2-ethylhexanoate)	136-52-7	< 0.1
1,4-Naphthoquinone	130-15-4	< 0.05

**SECTION 4: First aid measures**
**4.1. Description of first aid measures**
**Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin contact**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye contact**

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

**If swallowed**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

Target organ effects. See Section 11 for additional details. Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

## **SECTION 5: Fire-fighting measures**

**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

**5.2. Special hazards arising from the substance or mixture**

Closed containers exposed to heat from fire may build pressure and explode.

**5.3. Special protective actions for fire-fighters**

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

**Hazchem Code:** •3Y

## **SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. **WARNING !** A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

**6.3. Methods and material for containment and cleaning up**

Contain spill. Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## **SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

Avoid breathing of dust created by cutting, sanding, grinding or machining. Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No

smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (eg. gloves, respirators...) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapour accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

## 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from acids. Store away from oxidising agents.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Ethylbenzene	100-41-4	ACGIH	TWA:20 ppm	A3: Confirmed animal carcin., Ototoxicant
Ethylbenzene	100-41-4	Australia OELs	TWA(8 hours):434 mg/m3(100 ppm);STEL(15 minutes):543 mg/m3(125 ppm)	
Styrene	100-42-5	ACGIH	TWA:10 ppm;STEL:20 ppm	A3: Confirmed animal carcin., Ototoxicant
Styrene	100-42-5	Australia OELs	TWA(8 hours): 213 mg/m3 (50 ppm), STEL(15 minutes): 426 mg/m3 (100 ppm).	
Synthetic Crystalline-Free Silica Gel	112926-00-8	Australia OELs	TWA(Inspirable fraction)(8 hours):10 mg/m3	
Limestone	1317-65-3	Australia OELs	TWA(Inspirable dust)(8 hours):10 mg/m3	
Titanium dioxide	13463-67-7	ACGIH	TWA(Respirable nanoscale particles):0.2 mg/m3;TWA(Respirable finescale particles):2.5 mg/m3	A3: Confirmed animal carcinogen.
Titanium dioxide	13463-67-7	Australia OELs	TWA(Inspirable dust)(8 hours):10 mg/m3	
Talc	14807-96-6	ACGIH	TWA(respirable fraction):2 mg/m3	A4: Not class. as human carcin
Talc	14807-96-6	Australia OELs	TWA(8 hours):2.5 mg/m3	
Quartz	14808-60-7	ACGIH	TWA(respirable fraction):0.025 mg/m3	A2: Suspected human carcin.
Quartz	14808-60-7	Australia OELs	TWA(8 hours):0.1 mg/m3;Limit value not established:	
Magnesium Carbonate	546-93-0	Australia OELs	TWA(Inspirable dust)(8 hours):10 mg/m3	
Inert Filler	Trade Secret	Manufacturer determined	TWA(as non-fibrous, respirable)(8 hours):3 mg/m3;TWA(as non-fibrous,	

			inhalable fraction)(8 hours):10 mg/m <sup>3</sup>	
Inert Filler	Trade Secret	ACGIH	TWA(as fiber):0.2 fiber/cc	A2: Suspected human carcin.
Inert Filler	Trade Secret	ACGIH	TWA(as fiber):1 fiber/cc	A3: Confirmed animal carcinogen.
Inert Filler	Trade Secret	ACGIH	TWA(as fiber):1 fiber/cc	A4: Not class. as human carcin
Inert Filler	Trade Secret	ACGIH	TWA(inhalable fraction):5 mg/m <sup>3</sup>	A4: Not class. as human carcin
Inert Filler	Trade Secret	Australia OELs	TWA(as fiber)(8 hours):0.5 fibers/ml	
Inert Filler	Trade Secret	Australia OELs	TWA(as fiber)(8 hours):0.5 fibers/ml;TWA(8 hours):0.5 fibers/ml	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

Australia OELs : Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Sen: Sensitiser

Sk: Absorption through the skin may be a significant source of exposure.

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Indirect vented goggles.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Fluoroelastomer

Polyvinyl alcohol (PVA).

Polymer laminate

Select and use gloves according to AS/NZ 2161.

#### Respiratory protection



An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Select and use respirators according to AS/NZS 1715. Respirators should comply with AS/NZS 1716 performance specifications. For information about respirators, call 3M on 1800 024 464.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Colour	White
Odour	Styrene
Odour threshold	No data available.
pH	No data available.
Melting point/Freezing point	No data available.
Boiling point/Initial boiling point/Boiling range	No data available.
Flash point	32.2 °C
Evaporation rate	<=1 [Ref Std:ETHER=1]
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	0.9 - 1.1 %
Flammable Limits(UEL)	6.1 - 6.8 %
Vapour pressure	No data available.
Vapor Density and/or Relative Vapor Density	>=1 [Ref Std:AIR=1]
Density	1.07 g/ml
Relative density	1.07 [Ref Std:WATER=1]
Water solubility	Nil
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Autoignition temperature	No data available.
Decomposition temperature	No data available.
Viscosity/Kinematic Viscosity	160,000 mPa-s
Volatile organic compounds (VOC)	20.5 % weight [Test Method:calculated per CARB title 2]
Percent volatile	21.4 %
VOC less H <sub>2</sub> O & exempt solvents	228 g/l [Test Method:calculated SCAQMD rule 443.1]
Molecular weight	No data available.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

### 10.2 Chemical stability

Stable.

### 10.3. Conditions to avoid

Not determined

### 10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

**10.5 Incompatible materials**

Strong acids.

Alkali and alkaline earth metals.

Strong oxidising agents.

Avoid contact with strong acids strong alkalis and oxidizers.

**10.6 Hazardous decomposition products**

<u>Substance</u>	<u>Condition</u>
Carbon monoxide.	Not specified.
Carbon dioxide.	Not specified.

**SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

**11.1 Information on Toxicological effects****Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

**Inhalation**

May be harmful if inhaled. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

**Skin contact**

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

**Eye contact**

Moderate eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

**Ingestion**

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

**Additional Health Effects:****Single exposure may cause target organ effects:**

Auditory effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears. Liver effects: Signs/symptoms may include loss of appetite, weight loss, fatigue, weakness, abdominal tenderness and jaundice.

**Prolonged or repeated exposure may cause target organ effects:**

Pneumoconiosis: Sign/symptoms may include persistent cough, breathlessness, chest pain, increased amounts of sputum, and changes in lung function tests. Ocular effects: Signs/symptoms may include blurred or significantly impaired vision.

Auditory effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears. Liver effects: Signs/symptoms may include loss of appetite, weight loss, fatigue, weakness, abdominal tenderness and jaundice.

**Carcinogenicity:**

Contains a chemical or chemicals which can cause cancer.

### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

### Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >20 - =50 mg/l
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
Talc	Dermal		LD50 estimated to be > 5,000 mg/kg
Talc	Ingestion		LD50 estimated to be > 5,000 mg/kg
Styrene	Dermal	Rat	LD50 > 2,000 mg/kg
Styrene	Inhalation-Vapour (4 hours)	Rat	LC50 11.8 mg/l
Styrene	Ingestion	Rat	LD50 5,000 mg/kg
Magnesium Carbonate	Dermal	Professional judgement	LD50 estimated to be 2,000 - 5,000 mg/kg
Magnesium Carbonate	Ingestion	Rat	LD50 > 2,000 mg/kg
Polyester Polymer	Dermal		LD50 estimated to be > 5,000 mg/kg
Polyester Polymer	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Inert Filler	Dermal		LD50 estimated to be > 5,000 mg/kg
Inert Filler	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Limestone	Dermal	Rat	LD50 > 2,000 mg/kg
Limestone	Inhalation-Dust/Mist (4 hours)	Rat	LC50 3 mg/l
Limestone	Ingestion	Rat	LD50 6,450 mg/kg
Synthetic Crystalline-Free Silica Gel	Dermal	Rabbit	LD50 > 5,000 mg/kg
Synthetic Crystalline-Free Silica Gel	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Synthetic Crystalline-Free Silica Gel	Ingestion	Rat	LD50 > 5,110 mg/kg
Titanium dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
Chlorite-group minerals	Dermal		LD50 estimated to be > 5,000 mg/kg
Chlorite-group minerals	Ingestion		LD50 estimated to be > 5,000 mg/kg
Dolomite	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Dolomite	Ingestion	Rat	LD50 > 2,000 mg/kg
Ethylbenzene	Dermal	Rabbit	LD50 15,433 mg/kg
Ethylbenzene	Inhalation-Vapour (4 hours)	Rat	LC50 17.4 mg/l
Ethylbenzene	Ingestion	Rat	LD50 4,769 mg/kg
Quartz	Dermal		LD50 estimated to be > 5,000 mg/kg
Quartz	Ingestion		LD50 estimated to be > 5,000 mg/kg
1,4-Naphthoquinone	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.046 mg/l
1,4-Naphthoquinone	Ingestion	Rat	LD50 124 mg/kg
Cobalt bis(2-ethylhexanoate)	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Cobalt bis(2-ethylhexanoate)	Ingestion	Rat	LD50 3,129 mg/kg

ATE = acute toxicity estimate

### Skin Corrosion/Irritation

Name	Species	Value
------	---------	-------

Talc	Rabbit	No significant irritation
Styrene	Professional judgement	Mild irritant
Magnesium Carbonate	In vitro data	No significant irritation
Inert Filler	Professional judgement	No significant irritation
Limestone	Rabbit	No significant irritation
Synthetic Crystalline-Free Silica Gel	Rabbit	No significant irritation
Titanium dioxide	Rabbit	No significant irritation
Chlorite-group minerals	Professional judgement	No significant irritation
Dolomite	Professional judgement	No significant irritation
Ethylbenzene	Rabbit	Mild irritant
Quartz	Professional judgement	No significant irritation
1,4-Naphthoquinone	Rabbit	Corrosive
Cobalt bis(2-ethylhexanoate)	In vitro data	No significant irritation

### Serious Eye Damage/Irritation

Name	Species	Value
Talc	Rabbit	No significant irritation
Styrene	Professional judgement	Moderate irritant
Magnesium Carbonate	Rabbit	Mild irritant
Inert Filler	Professional judgement	No significant irritation
Limestone	Rabbit	No significant irritation
Synthetic Crystalline-Free Silica Gel	Rabbit	No significant irritation
Titanium dioxide	Rabbit	No significant irritation
Chlorite-group minerals	Professional judgement	No significant irritation
Dolomite	Professional judgement	No significant irritation
Ethylbenzene	Rabbit	Moderate irritant
1,4-Naphthoquinone	similar health hazards	Corrosive
Cobalt bis(2-ethylhexanoate)	Rabbit	Severe irritant

### Skin Sensitisation

Name	Species	Value
Styrene	Guinea pig	Not classified
Synthetic Crystalline-Free Silica Gel	Human and animal	Not classified
Titanium dioxide	Human and animal	Not classified
Ethylbenzene	Human	Not classified
1,4-Naphthoquinone	Guinea pig	Sensitising
Cobalt bis(2-ethylhexanoate)	similar compounds	Sensitising

### Respiratory Sensitisation

Name	Species	Value
Talc	Human	Not classified
Cobalt bis(2-ethylhexanoate)	similar compounds	Sensitising

### Germ Cell Mutagenicity

Name	Route	Value
Talc	In Vitro	Not mutagenic
Talc	In vivo	Not mutagenic
Styrene	In Vitro	Some positive data exist, but the data are not sufficient for classification
Styrene	In vivo	Some positive data exist, but the data are not sufficient for classification
Inert Filler	In Vitro	Some positive data exist, but the data are not

		sufficient for classification
Synthetic Crystalline-Free Silica Gel	In Vitro	Not mutagenic
Titanium dioxide	In Vitro	Not mutagenic
Titanium dioxide	In vivo	Not mutagenic
Ethylbenzene	In vivo	Not mutagenic
Ethylbenzene	In Vitro	Some positive data exist, but the data are not sufficient for classification
Quartz	In Vitro	Some positive data exist, but the data are not sufficient for classification
Quartz	In vivo	Some positive data exist, but the data are not sufficient for classification
1,4-Naphthoquinone	In vivo	Not mutagenic
1,4-Naphthoquinone	In Vitro	Some positive data exist, but the data are not sufficient for classification

### Carcinogenicity

Name	Route	Species	Value
Talc	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
Styrene	Ingestion	Mouse	Carcinogenic.
Styrene	Inhalation	Human and animal	Carcinogenic.
Inert Filler	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Synthetic Crystalline-Free Silica Gel	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
Titanium dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium dioxide	Inhalation	Rat	Carcinogenic.
Ethylbenzene	Inhalation	Multiple animal species	Carcinogenic.
Quartz	Inhalation	Human and animal	Carcinogenic.
Cobalt bis(2-ethylhexanoate)	Inhalation	similar compounds	Carcinogenic.

### Reproductive Toxicity

#### Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Talc	Ingestion	Not classified for development	Rat	NOAEL 1,600 mg/kg	during organogenesis
Styrene	Ingestion	Not classified for female reproduction	Rat	NOAEL 21 mg/kg/day	3 generation
Styrene	Inhalation	Not classified for female reproduction	Rat	NOAEL 2.1 mg/l	2 generation
Styrene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.1 mg/l	2 generation
Styrene	Ingestion	Not classified for male reproduction	Rat	NOAEL 400 mg/kg/day	60 days
Styrene	Ingestion	Not classified for development	Rat	NOAEL 400 mg/kg/day	during gestation
Styrene	Inhalation	Not classified for development	Multiple animal species	NOAEL 2.1 mg/l	during gestation
Limestone	Ingestion	Not classified for development	Rat	NOAEL 625 mg/kg/day	prematings & during gestation
Synthetic Crystalline-Free Silica Gel	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Synthetic Crystalline-Free Silica Gel	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Synthetic Crystalline-Free Silica Gel	Ingestion	Not classified for development	Rat	NOAEL 1,350	during organogenesis

				mg/kg/day	
Ethylbenzene	Inhalation	Not classified for development	Rat	NOAEL 4.3 mg/l	prematuring & during gestation
1,4-Naphthoquinone	Ingestion	Not classified for female reproduction	Rat	NOAEL 2 mg/kg/day	prematuring into lactation
1,4-Naphthoquinone	Ingestion	Not classified for male reproduction	Rat	NOAEL 2 mg/kg/day	42 days
1,4-Naphthoquinone	Ingestion	Not classified for development	Rat	NOAEL 2 mg/kg/day	prematuring & during gestation
Cobalt bis(2-ethylhexanoate)	Ingestion	Toxic to development	similar compounds	NOAEL Not available	
Cobalt bis(2-ethylhexanoate)	Ingestion	Toxic to male reproduction	similar compounds	NOAEL Not available	
Cobalt bis(2-ethylhexanoate)	Inhalation	Toxic to male reproduction	similar compounds	NOAEL Not available	

### Target Organ(s)

#### Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Styrene	Inhalation	auditory system	Causes damage to organs	Multiple animal species	LOAEL 4.3 mg/l	not available
Styrene	Inhalation	liver	Causes damage to organs	Mouse	LOAEL 2.1 mg/l	not available
Styrene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	occupational exposure
Styrene	Inhalation	respiratory irritation	May cause respiratory irritation	Human and animal	NOAEL Not available	
Styrene	Inhalation	endocrine system	Not classified	Rat	NOAEL Not available	not available
Styrene	Inhalation	kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2.1 mg/l	not available
Limestone	Inhalation	respiratory system	Not classified	Rat	NOAEL 0.812 mg/l	90 minutes
Ethylbenzene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Ethylbenzene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available	
Ethylbenzene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
1,4-Naphthoquinone	Inhalation	respiratory irritation	May cause respiratory irritation	similar health hazards	NOAEL Not available	
Cobalt bis(2-ethylhexanoate)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL not available	

#### Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
------	-------	-----------------	-------	---------	-------------	-------------------

Talc	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Talc	Inhalation	pulmonary fibrosis   respiratory system	Not classified	Rat	NOAEL 18 mg/m3	113 weeks
Styrene	Inhalation	auditory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL not available	occupational exposure
Styrene	Inhalation	eyes	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Styrene	Inhalation	liver	May cause damage to organs though prolonged or repeated exposure	Mouse	LOAEL 0.85 mg/l	13 weeks
Styrene	Inhalation	nervous system	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	LOAEL 1.1 mg/l	not available
Styrene	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 0.85 mg/l	7 days
Styrene	Inhalation	endocrine system	Not classified	Rat	NOAEL 0.6 mg/l	10 days
Styrene	Inhalation	respiratory system	Not classified	Multiple animal species	LOAEL 0.09 mg/l	not available
Styrene	Inhalation	heart   gastrointestinal tract   bone, teeth, nails, and/or hair   muscles   kidney and/or bladder	Not classified	Multiple animal species	NOAEL 4.3 mg/l	2 years
Styrene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 500 mg/kg/day	8 weeks
Styrene	Ingestion	immune system	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL Not available	not available
Styrene	Ingestion	liver   kidney and/or bladder	Not classified	Rat	NOAEL 677 mg/kg/day	6 months
Styrene	Ingestion	hematopoietic system	Not classified	Dog	NOAEL 600 mg/kg/day	470 days
Styrene	Ingestion	heart   respiratory system	Not classified	Rat	NOAEL 35 mg/kg/day	105 weeks
Inert Filler	Inhalation	respiratory system	Not classified	Human	NOAEL not available	occupational exposure
Limestone	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Synthetic	Inhalation	respiratory	Not classified	Human	NOAEL Not	occupational

Crystalline-Free Silica Gel		system   silicosis			available	exposure
Titanium dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Ethylbenzene	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	2 years
Ethylbenzene	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 1.1 mg/l	103 weeks
Ethylbenzene	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 3.4 mg/l	28 days
Ethylbenzene	Inhalation	auditory system	Not classified	Rat	NOAEL 2.4 mg/l	5 days
Ethylbenzene	Inhalation	endocrine system	Not classified	Mouse	NOAEL 3.3 mg/l	103 weeks
Ethylbenzene	Inhalation	gastrointestinal tract	Not classified	Rat	NOAEL 3.3 mg/l	2 years
Ethylbenzene	Inhalation	bone, teeth, nails, and/or hair   muscles	Not classified	Multiple animal species	NOAEL 4.2 mg/l	90 days
Ethylbenzene	Inhalation	heart   immune system   respiratory system	Not classified	Multiple animal species	NOAEL 3.3 mg/l	2 years
Ethylbenzene	Ingestion	liver   kidney and/or bladder	Not classified	Rat	NOAEL 680 mg/kg/day	6 months
Quartz	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
1,4-Naphthoquinone	Ingestion	heart   endocrine system   gastrointestinal tract   bone, teeth, nails, and/or hair   hematopoietic system   liver   immune system   muscles   nervous system   eyes   kidney and/or bladder   respiratory system	Not classified	Rat	NOAEL 2 mg/kg/day	42 days
Cobalt bis(2-ethylhexanoate)	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	similar compounds	NOAEL Not available	



**Aspiration Hazard**

Name	Value
Styrene	Aspiration hazard
Ethylbenzene	Aspiration hazard

**Exposure Levels**

Refer Section 8.1 **Control Parameters** of this Safety Data Sheet.

**Interactive Effects**

Not determined.

## SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

**12.1. Toxicity****Acute aquatic hazard:**

GHS Acute 3: Harmful to aquatic life.

**Chronic aquatic hazard:**

GHS Chronic 3: Harmful to aquatic life with long lasting effects.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Resin Polymer	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Talc	14807-96-6	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Styrene	100-42-5	Activated sludge	Experimental	30 minutes	EC50	500 mg/l
Styrene	100-42-5	Fathead minnow	Experimental	96 hours	LC50	4.02 mg/l
Styrene	100-42-5	Green algae	Experimental	72 hours	EC50	4.9 mg/l
Styrene	100-42-5	Water flea	Experimental	48 hours	EC50	4.7 mg/l
Styrene	100-42-5	Green algae	Experimental	96 hours	EC10	0.28 mg/l
Styrene	100-42-5	Water flea	Experimental	21 days	NOEC	1.01 mg/l
Inert Filler	Trade Secret	Green algae	Experimental	72 hours	EC50	>1,000 mg/l
Inert Filler	Trade Secret	Water flea	Experimental	72 hours	EC50	>1,000 mg/l
Inert Filler	Trade Secret	Zebra Fish	Experimental	96 hours	LC50	>1,000 mg/l
Inert Filler	Trade Secret	Green algae	Experimental	72 hours	NOEC	>=1,000 mg/l
Magnesium Carbonate	546-93-0	Activated sludge	Estimated	3 hours	EC50	>900 mg/l
Magnesium Carbonate	546-93-0	Fathead minnow	Estimated	96 hours	LC50	1,880 mg/l
Magnesium Carbonate	546-93-0	Green algae	Estimated	72 hours	EC50	>100 mg/l
Magnesium Carbonate	546-93-0	Water flea	Estimated	48 hours	LC50	486 mg/l
Magnesium Carbonate	546-93-0	Green algae	Estimated	72 hours	NOEC	100 mg/l
Magnesium Carbonate	546-93-0	Water flea	Estimated	21 days	EC10	284 mg/l
Polyester Polymer	Trade Secret	N/A	Data not available or insufficient for	N/A	N/A	N/A

			classification			
Limestone	1317-65-3	Green algae	Estimated	72 hours	EC50	>100 mg/l
Limestone	1317-65-3	Rainbow trout	Estimated	96 hours	LC50	>100 mg/l
Limestone	1317-65-3	Water flea	Estimated	48 hours	EC50	>100 mg/l
Limestone	1317-65-3	Green algae	Estimated	72 hours	EC10	>100 mg/l
Synthetic Crystalline-Free Silica Gel	112926-00-8	Green algae	Analogous Compound	72 hours	ErC50	>173.1 mg/l
Synthetic Crystalline-Free Silica Gel	112926-00-8	Sediment organism	Experimental	96 hours	EC50	8,500 mg/kg (Dry Weight)
Synthetic Crystalline-Free Silica Gel	112926-00-8	Water flea	Experimental	24 hours	EL50	>10,000 mg/l
Synthetic Crystalline-Free Silica Gel	112926-00-8	Zebra Fish	Experimental	96 hours	LL50	>10,000 mg/l
Synthetic Crystalline-Free Silica Gel	112926-00-8	Green algae	Analogous Compound	72 hours	NOEC	173.1 mg/l
Synthetic Crystalline-Free Silica Gel	112926-00-8	Water flea	Analogous Compound	21 days	NOEC	68 mg/l
Synthetic Crystalline-Free Silica Gel	112926-00-8	Activated sludge	Analogous Compound	3 hours	EC50	>1,000 mg/l
Titanium dioxide	13463-67-7	Activated sludge	Experimental	3 hours	NOEC	>=1,000 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	EC50	>10,000 mg/l
Titanium dioxide	13463-67-7	Fathead minnow	Experimental	96 hours	LC50	>100 mg/l
Titanium dioxide	13463-67-7	Water flea	Experimental	48 hours	EC50	>100 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	NOEC	5,600 mg/l
Chlorite-group minerals	1318-59-8	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Dolomite	16389-88-1	Water flea	Estimated	48 hours	EC50	190 mg/l
Dolomite	16389-88-1	Western Mosquitofish	Estimated	96 hours	LC50	>100 mg/l
Dolomite	16389-88-1	Rainbow trout	Estimated	21 days	NOEC	>100 mg/l
Ethylbenzene	100-41-4	Activated sludge	Experimental	49 hours	EC50	130 mg/l
Ethylbenzene	100-41-4	Atlantic Silverside	Experimental	96 hours	LC50	5.1 mg/l
Ethylbenzene	100-41-4	Green algae	Experimental	96 hours	EC50	3.6 mg/l
Ethylbenzene	100-41-4	Mysid Shrimp	Experimental	96 hours	LC50	2.6 mg/l
Ethylbenzene	100-41-4	Rainbow trout	Experimental	96 hours	LC50	4.2 mg/l
Ethylbenzene	100-41-4	Water flea	Experimental	48 hours	EC50	1.8 mg/l
Ethylbenzene	100-41-4	Water flea	Experimental	7 days	NOEC	0.96 mg/l
Quartz	14808-60-7	Green algae	Estimated	72 hours	EC50	440 mg/l
Quartz	14808-60-7	Water flea	Estimated	48 hours	EC50	7,600 mg/l
Quartz	14808-60-7	Zebra Fish	Estimated	96 hours	LC50	5,000 mg/l
Quartz	14808-60-7	Green algae	Estimated	72 hours	NOEC	60 mg/l
Cobalt bis(2-ethylhexanoate)	136-52-7	Activated sludge	Estimated	30 minutes	EC50	703 mg/l
Cobalt bis(2-ethylhexanoate)	136-52-7	Algae or other aquatic plants	Estimated	7 days	EC50	0.14 mg/l
Cobalt bis(2-ethylhexanoate)	136-52-7	Green algae	Estimated	72 hours	ErC50	0.84 mg/l
Cobalt bis(2-ethylhexanoate)	136-52-7	Rainbow trout	Estimated	96 hours	LC50	8.9 mg/l
Cobalt bis(2-ethylhexanoate)	136-52-7	Water flea	Estimated	48 hours	LC50	3.5 mg/l
Cobalt bis(2-ethylhexanoate)	136-52-7	Algae or other aquatic plants	Estimated	7 days	EC10	0.007 mg/l
Cobalt bis(2-ethylhexanoate)	136-52-7	Fathead minnow	Estimated	34 days	NOEC	1.2 mg/l
Cobalt bis(2-ethylhexanoate)	136-52-7	Green algae	Estimated	72 hours	EC10	0.135 mg/l
1,4-Naphthoquinone	130-15-4	Activated sludge	Experimental	3 hours	EC50	5.94 mg/l

1,4-Naphthoquinone	130-15-4	Green algae	Experimental	72 hours	EC50	0.42 mg/l
1,4-Naphthoquinone	130-15-4	Medaka	Experimental	96 hours	LC50	0.045 mg/l
1,4-Naphthoquinone	130-15-4	Water flea	Experimental	48 hours	EC50	0.026 mg/l
1,4-Naphthoquinone	130-15-4	Green algae	Experimental	72 hours	NOEC	0.07 mg/l

## 12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Resin Polymer	Trade Secret	Data not available-insufficient	N/A	N/A	N/A	N/A
Talc	14807-96-6	Data not available-insufficient	N/A	N/A	N/A	N/A
Styrene	100-42-5	Experimental Biodegradation	28 days	BOD	70.9 %BOD/ThOD	
Styrene	100-42-5	Experimental Photolysis		Photolytic half-life (in air)	6.64 hours (t 1/2)	
Inert Filler	Trade Secret	Data not available-insufficient	N/A	N/A	N/A	N/A
Magnesium Carbonate	546-93-0	Data not available-insufficient	N/A	N/A	N/A	N/A
Polyester Polymer	Trade Secret	Data not available-insufficient	N/A	N/A	N/A	N/A
Limestone	1317-65-3	Data not available-insufficient	N/A	N/A	N/A	N/A
Synthetic Crystalline-Free Silica Gel	112926-00-8	Data not available-insufficient	N/A	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Data not available-insufficient	N/A	N/A	N/A	N/A
Chlorite-group minerals	1318-59-8	Data not available-insufficient	N/A	N/A	N/A	N/A
Dolomite	16389-88-1	Data not available-insufficient	N/A	N/A	N/A	N/A
Ethylbenzene	100-41-4	Experimental Biodegradation	28 days	CO2 evolution	70-80 %CO2 evolution/THCO2 evolution	ISO 14593 Inorg C Headspace
Ethylbenzene	100-41-4	Experimental Photolysis		Photolytic half-life (in air)	4.26 days (t 1/2)	
Quartz	14808-60-7	Data not available-insufficient	N/A	N/A	N/A	N/A
Cobalt bis(2-ethylhexanoate)	136-52-7	Data not available-insufficient	N/A	N/A	N/A	N/A
1,4-Naphthoquinone	130-15-4	Experimental Biodegradation	28 days	BOD	0 %BOD/ThOD	OECD 301F - Manometric respirometry
1,4-Naphthoquinone	130-15-4	Experimental Hydrolysis		Hydrolytic half-life	12 days (t 1/2)	

## 12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Resin Polymer	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Talc	14807-96-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Styrene	100-42-5	Experimental Bioconcentration		Log Kow	2.96	
Inert Filler	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Magnesium Carbonate	546-93-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Polyester Polymer	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Limestone	1317-65-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Synthetic Crystalline-Free Silica Gel	112926-00-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Experimental BCF - Fish	42 days	Bioaccumulation factor	9.6	
Chlorite-group minerals	1318-59-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Dolomite	16389-88-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Ethylbenzene	100-41-4	Experimental BCF - Fish	42 days	Bioaccumulation factor	1	
Quartz	14808-60-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Cobalt bis(2-ethylhexanoate)	136-52-7	Analogous Compound BCF - Fish	63 days	Bioaccumulation factor	190	
1,4-Naphthoquinone	130-15-4	Experimental Bioconcentration		Log Kow	1.77	

#### 12.4. Mobility in soil

Please contact manufacturer for more details

#### 12.5 Other adverse effects

No information available.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility.

## SECTION 14: Transport Information

**Australian Dangerous Goods Code (ADG) - Road/Rail Transport**

**UN No.:** UN1866

**Proper shipping name:** RESIN SOLUTION

**Class/Division:** 3

**Sub Risk:** Not applicable.

**Packing Group:** III

**Special Instructions:** Limited quantity may apply

**Hazchem Code:** •3Y

**IERG:** 14

**International Air Transport Association (IATA) - Air Transport**

**UN No.:** UN1866

**Proper shipping name:** RESIN SOLUTION

**Class/Division:** 3

**Sub Risk:** Not applicable.

**Packing Group:** III

**Special Instructions:** Forbidden, package size exceeds IATA quantity limitations

**International Maritime Dangerous Goods Code (IMDG)- Marine Transport**

**UN No.:** UN1866

**Proper shipping name:** RESIN SOLUTION

**Class/Division:** 3

**Sub Risk:** Not applicable.

**Packing Group:** III

**Marine Pollutant:** Not applicable.

**Special Instructions:** Limited quantity may apply

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **Australian Inventory Status:**

All components of this product are listed on or exempt from the Australian Inventory of Industrial Chemicals (AIIC). Conditions may apply prior to introduction for direct importers of this product, Please contact 3M Australia on 136 136 for further details.

**Poison Schedule:** This product is intended for Industrial or Professional Use only and therefore is not packaged and labelled in accordance with the requirements of the Standard for the Uniform Scheduling of Medicines and Poisons.

## SECTION 16: Other information

#### **Revision information:**

Complete document review.

**DISCLAIMER:** The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.



## Safety Data Sheet

Copyright, 2024, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	29-5993-0	<b>Version number:</b>	4.00
<b>Issue Date:</b>	01/12/2024	<b>Supersedes date:</b>	24/08/2021

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Cream Hardener (Red, White & Blue)

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Automotive, hardener for body fillers & glazes

For Industrial or Professional use only.

#### 1.3. Supplier's details

<b>Address:</b>	3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113
<b>Telephone:</b>	136 136
<b>E Mail:</b>	productinfo.au@mmm.com
<b>Website:</b>	www.3m.com.au

#### 1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

### SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

#### 2.1. Classification of the substance or mixture

Organic Peroxide: Type E.

Serious Eye Damage/Irritation: Category 2.

Skin Sensitizer: Category 1B.

Specific Target Organ Toxicity (single exposure): Category 2.

#### 2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

## Signal word

Warning

## Symbols

Flame | Exclamation mark | Health Hazard |

## Pictograms



## Hazard statements

H242	Heating may cause a fire.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H371	May cause damage to organs: cardiovascular system   kidney/urinary tract   nervous system   respiratory system.

## Precautionary statements

### General:

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.

### Prevention:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P234	Keep only in original packaging.
P235	Keep cool.
P240	Ground and bond container and receiving equipment.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280B	Wear protective gloves and eye/face protection.

### Response:

P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P311	IF exposed or concerned: Call a POISON CENTER or doctor/physician.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.

### Storage:

P403	Store in a well-ventilated place.
P405	Store locked up.
P410	Protect from sunlight.
P411	Store at temperatures not exceeding 32 °C.
P420	Store separately.

**Disposal:**

P501

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**2.3. Other assigned/identified product hazards**

None known.

**2.4. Other hazards which do not result in classification**

May be harmful in contact with skin.

Very toxic to aquatic life with long lasting effects.

**SECTION 3: Composition/information on ingredients**

This material is a mixture.

<b>Ingredient</b>	<b>CAS Nbr</b>	<b>% by Weight</b>
Benzoyl Peroxide	94-36-0	30 - 60
Water	7732-18-5	10 - 30
Benzoic Acid, C9-11-Branched Alkyl Esters	131298-44-7	10 - 30
Zinc Stearate	557-05-1	1 - 10
Calcium Sulfate	7778-18-9	1 - 10
Ethylene Glycol	107-21-1	<= 7.5
Iron Oxide (Fe <sub>2</sub> O <sub>3</sub> )	1309-37-1	<= 5
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	9038-95-3	<= 5
Ferric Ammonium Ferrocyanide	25869-00-5	<= 1
Ferric Ferrocyanide	14038-43-8	<= 1

**SECTION 4: First aid measures****4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin contact**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye contact**

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

**If swallowed**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

Allergic skin reaction (redness, swelling, blistering, and itching). Target organ effects. See Section 11 for additional details.

**4.3. Indication of any immediate medical attention and special treatment required**

This product contains ethylene glycol. If there is reasonable suspicion of ethylene glycol poisoning, intravenous (IV) administration with either fomepizole (preferred) or ethanol (if fomepizole is unavailable) should be considered as part of the medical management.

**SECTION 5: Fire-fighting measures****5.1. Suitable extinguishing media**



In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### **5.2. Special hazards arising from the substance or mixture**

Closed containers exposed to heat from fire may build pressure and explode. Part of the oxygen for combustion is supplied by the peroxide itself.

### **5.3. Special protective actions for fire-fighters**

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

**Hazchem Code:** 1W

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Eliminate all ignition sources if safe to do so. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice.

**WARNING !** A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### **6.2. Environmental precautions**

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

### **6.3. Methods and material for containment and cleaning up**

Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## **SECTION 7: Handling and storage**

### **7.1. Precautions for safe handling**

Do not use in a confined area with minimal air exchange. Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

### **7.2. Conditions for safe storage including any incompatibilities**

Keep container tightly closed. Protect from sunlight. Store away from heat. Store at temperatures not exceeding 32C. Keep cool. Keep only in original container. Store away from other materials. Keep/store away from clothing and other combustible materials.

## **SECTION 8: Exposure controls/personal protection**

### **8.1 Control parameters**

#### **Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

<b>Ingredient</b>	<b>CAS Nbr</b>	<b>Agency</b>	<b>Limit type</b>	<b>Additional comments</b>
Ethylene Glycol	107-21-1	ACGIH	TWA(Vapor fraction):25	A4: Not class. as human

			ppm;STEL(Vapor fraction):50 ppm;STEL(Inhalable aerosol):10 mg/m3	carcin
Ethylene Glycol	107-21-1	Australia OELs	TWA(as vapor)(8 hours):52 mg/m3(20 ppm);TWA(as particulate)(8 hours):10 mg/m3;STEL(as vapor)(15 minutes):104 mg/m3(40 ppm)	SKIN
Iron Oxide (Fe2O3)	1309-37-1	ACGIH	TWA(respirable fraction):5 mg/m3	A4: Not class. as human carcin
Iron Oxide (Fe2O3)	1309-37-1	Australia OELs	TWA(as Fe, fume)(8 hours):5 mg/m3	
CYANIDES	14038-43-8	Australia OELs	TWA(as CN)(8 hours):5 mg/m3	SKIN
Calcium Sulfate	7778-18-9	ACGIH	TWA(inhalable fraction):10 mg/m3	
Calcium Sulfate	7778-18-9	Australia OELs	TWA(Inspirable dust)(8 hours):10 mg/m3	
Benzoyl Peroxide	94-36-0	ACGIH	TWA:5 mg/m3	A4: Not class. as human carcin
Benzoyl Peroxide	94-36-0	Australia OELs	TWA(8 hours):5 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

Australia OELs : Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Sen: Sensitiser

Sk: Absorption through the skin may be a significant source of exposure.

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Provide ventilation adequate to maintain dust concentration below minimum explosive concentrations. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

if this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Select and use gloves according to AS/NZ 2161.

### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Select and use respirators according to AS/NZS 1715. Respirators should comply with AS/NZS 1716 performance specifications. For information about respirators, call 3M on 1800 024 464.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Solid.
<b>Specific Physical Form:</b>	Paste
<b>Colour</b>	Red
<b>Odour</b>	Slight Ester
<b>Odour threshold</b>	<i>No data available.</i>
<b>pH</b>	<i>No data available.</i>
<b>Melting point/Freezing point</b>	<i>No data available.</i>
<b>Boiling point/Initial boiling point/Boiling range</b>	<i>No data available.</i>
<b>Flash point</b>	111 °C [ <i>Test Method</i> :Estimated]
<b>Evaporation rate</b>	<i>No data available.</i>
<b>Flammability</b>	Organic Peroxide: Type E.
<b>Flammable Limits(LEL)</b>	<i>Not applicable.</i>
<b>Flammable Limits(UEL)</b>	<i>Not applicable.</i>
<b>Vapour pressure</b>	<i>Not applicable.</i>
<b>Vapor Density and/or Relative Vapor Density</b>	<i>Not applicable.</i>
<b>Density</b>	1.2 g/cm3
<b>Relative density</b>	1.2 [ @ 25 °C ] [ <i>Ref Std</i> :WATER=1]
<b>Water solubility</b>	Negligible
<b>Solubility- non-water</b>	<i>No data available.</i>
<b>Partition coefficient: n-octanol/water</b>	<i>No data available.</i>
<b>Autoignition temperature</b>	<i>No data available.</i>
<b>Decomposition temperature</b>	<i>No data available.</i>
<b>Kinematic Viscosity</b>	<i>No data available.</i>
<b>Volatile organic compounds (VOC)</b>	0 - 90 g/l [ <i>Test Method</i> :calculated SCAQMD rule 443.1]
<b>Volatile organic compounds (VOC)</b>	0 % weight [ <i>Test Method</i> :calculated per CARB title 2]
<b>Percent volatile</b>	21 - 28.5 %
<b>VOC less H2O &amp; exempt solvents</b>	0 - 121 g/l [ <i>Test Method</i> :calculated SCAQMD rule 443.1]
<b>Molecular weight</b>	<i>Not applicable.</i>

<b>Particle Characteristics</b>	<i>Not applicable.</i>
---------------------------------	------------------------

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

### 10.2 Chemical stability

Stable. Stable unless exposed to heat, flames and drying conditions.

### 10.3. Conditions to avoid

Heat.

### 10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

### 10.5 Incompatible materials

Accelerators

### 10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide.	Not specified.
Carbon dioxide.	Not specified.
Toxic vapour, gas, particulate.	Not specified.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1 Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

#### Skin contact

May be harmful in contact with skin.

Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

#### Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

#### Additional Health Effects:

**Single exposure may cause target organ effects:**

Cardiac effects: Signs/symptoms may include irregular heartbeat (arrhythmia), changes in heart rate, damage to heart muscle, heart attack, and may be fatal. Neurological effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and changes in blood pressure and heart rate.

Respiratory effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and respiratory failure. Kidney/Bladder effects: Signs/symptoms may include changes in urine production, abdominal or lower back pain, increased protein in urine,

increased blood urea nitrogen (BUN), blood in urine, and painful urination.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >2,000 - =5,000 mg/kg
Overall product	Inhalation-Dust/Mist(4 hr)		No data available; calculated ATE >12.5 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Benzoyl Peroxide	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Benzoyl Peroxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 24.3 mg/l
Benzoyl Peroxide	Ingestion	Rat	LD50 > 5,000 mg/kg
Benzoic Acid, C9-11-Branched Alkyl Esters	Dermal	Rabbit	LD50 > 2,000 mg/kg
Benzoic Acid, C9-11-Branched Alkyl Esters	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.5 mg/l
Benzoic Acid, C9-11-Branched Alkyl Esters	Ingestion	Rat	LD50 > 5,000 mg/kg
Calcium Sulfate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.61 mg/l
Calcium Sulfate	Ingestion	Rat	LD50 > 1,581 mg/kg
Calcium Sulfate	Dermal	similar health hazards	LD50 estimated to be > 5,000 mg/kg
Zinc Stearate	Dermal	Rabbit	LD50 > 2,000 mg/kg
Zinc Stearate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 50 mg/l
Zinc Stearate	Ingestion	Rat	LD50 > 2,000 mg/kg
Ethylene Glycol	Ingestion	Human	LD50 1,600 mg/kg
Ethylene Glycol	Inhalation-Dust/Mist (4 hours)	Other	LC50 estimated to be 5 - 12.5 mg/l
Ethylene Glycol	Dermal	Rabbit	9,530 mg/kg
Iron Oxide (FE2O3)	Dermal	Not available	LD50 3,100 mg/kg
Iron Oxide (FE2O3)	Ingestion	Not available	LD50 3,700 mg/kg
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Dermal	Rabbit	LD50 > 16,960 mg/kg
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5 mg/l
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Ingestion	Rat	LD50 4,240 mg/kg
Ferric Ferrocyanide	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
Ferric Ammonium Ferrocyanide	Dermal	Rat	LD50 > 2,000 mg/kg
Ferric Ammonium Ferrocyanide	Ingestion	Rat	LD50 > 2,000 mg/kg
Ferric Ferrocyanide	Ingestion	similar compounds	LD50 > 2,000 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Benzoyl Peroxide	Rabbit	Minimal irritation
Benzoic Acid, C9-11-Branched Alkyl Esters	Rabbit	Minimal irritation
Calcium Sulfate	Rabbit	No significant irritation
Zinc Stearate	Rabbit	No significant irritation
Ethylene Glycol	Rabbit	Minimal irritation
Iron Oxide (FE2O3)	Rabbit	No significant irritation
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Rabbit	Minimal irritation
Ferric Ammonium Ferrocyanide	Rabbit	No significant irritation
Ferric Ferrocyanide	similar compounds	No significant irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
Benzoyl Peroxide	Rabbit	Severe irritant
Benzoic Acid, C9-11-Branched Alkyl Esters	Rabbit	Mild irritant
Calcium Sulfate	Rabbit	Mild irritant
Zinc Stearate	Rabbit	No significant irritation
Ethylene Glycol	Rabbit	Mild irritant
Iron Oxide (FE2O3)	Rabbit	No significant irritation
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Rabbit	No significant irritation
Ferric Ammonium Ferrocyanide	Rabbit	Mild irritant
Ferric Ferrocyanide	similar compounds	No significant irritation

**Skin Sensitisation**

Name	Species	Value
Benzoyl Peroxide	Guinea pig	Sensitising
Benzoic Acid, C9-11-Branched Alkyl Esters	Guinea pig	Not classified
Calcium Sulfate	Guinea pig	Not classified
Zinc Stearate	Human	Not classified
Ethylene Glycol	Human	Not classified
Iron Oxide (FE2O3)	Human	Not classified
Ferric Ammonium Ferrocyanide	Mouse	Not classified
Ferric Ferrocyanide	similar compounds	Not classified

**Respiratory Sensitisation**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity**

Name	Route	Value
Benzoyl Peroxide	In Vitro	Not mutagenic
Benzoyl Peroxide	In vivo	Not mutagenic
Benzoic Acid, C9-11-Branched Alkyl Esters	In Vitro	Not mutagenic
Benzoic Acid, C9-11-Branched Alkyl Esters	In vivo	Not mutagenic
Calcium Sulfate	In Vitro	Not mutagenic
Calcium Sulfate	In vivo	Not mutagenic
Zinc Stearate	In Vitro	Not mutagenic
Ethylene Glycol	In Vitro	Not mutagenic
Ethylene Glycol	In vivo	Not mutagenic
Iron Oxide (FE2O3)	In Vitro	Not mutagenic
Ferric Ammonium Ferrocyanide	In Vitro	Not mutagenic

**3M™ Cream Hardener (Red, White & Blue)**

Ferric Ferrocyanide	In Vitro	Not mutagenic
---------------------	----------	---------------

**Carcinogenicity**

Name	Route	Species	Value
Benzoyl Peroxide	Ingestion	Multiple animal species	Not carcinogenic
Benzoyl Peroxide	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Ethylene Glycol	Ingestion	Multiple animal species	Not carcinogenic
Iron Oxide (FE <sub>2</sub> O <sub>3</sub> )	Inhalation	Human	Some positive data exist, but the data are not sufficient for classification
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Ingestion	Rat	Not carcinogenic

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Benzoyl Peroxide	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
Benzoyl Peroxide	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	premating & during gestation
Benzoyl Peroxide	Ingestion	Not classified for development	Rat	NOAEL 500 mg/kg/day	premating & during gestation
Benzoic Acid, C9-11-Branched Alkyl Esters	Ingestion	Not classified for female reproduction	Rat	NOAEL 641 mg/kg/day	2 generation
Benzoic Acid, C9-11-Branched Alkyl Esters	Ingestion	Not classified for male reproduction	Rat	NOAEL 676 mg/kg/day	2 generation
Benzoic Acid, C9-11-Branched Alkyl Esters	Ingestion	Not classified for development	Rat	NOAEL 191 mg/kg/day	2 generation
Calcium Sulfate	Ingestion	Not classified for female reproduction	Rat	NOAEL 790 mg/kg/day	premating into lactation
Calcium Sulfate	Ingestion	Not classified for male reproduction	Rat	NOAEL 790 mg/kg/day	35 days
Calcium Sulfate	Ingestion	Not classified for development	Multiple animal species	NOAEL 1,600 mg/kg/day	during organogenesis
Ethylene Glycol	Dermal	Not classified for development	Mouse	NOAEL 3,549 mg/kg/day	during organogenesis
Ethylene Glycol	Ingestion	Not classified for development	Mouse	LOAEL 750 mg/kg/day	during organogenesis
Ethylene Glycol	Inhalation	Not classified for development	Mouse	NOAEL 1,000 mg/kg/day	during organogenesis
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Inhalation	Not classified for male reproduction	Rat	NOAEL 1 mg/l	2 weeks

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
------	-------	-----------------	-------	---------	-------------	-------------------

Ethylene Glycol	Ingestion	heart   nervous system   kidney and/or bladder   respiratory system	Causes damage to organs	Human	NOAEL Not available	poisoning and/or abuse
Ethylene Glycol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Ethylene Glycol	Ingestion	liver	Not classified	Human	NOAEL Not available	poisoning and/or abuse
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Ingestion	nervous system	Not classified	Rat	NOAEL Not available	

#### Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Benzoic Acid, C9-11- Branched Alkyl Esters	Ingestion	heart   skin   endocrine system   gastrointestinal tract   bone, teeth, nails, and/or hair   hematopoietic system   liver   immune system   muscles   nervous system   eyes   kidney and/or bladder   respiratory system   vascular system	Not classified	Rat	NOAEL 619 mg/kg/day	91 days
Calcium Sulfate	Ingestion	liver   kidney and/or bladder   heart   endocrine system   gastrointestinal tract   hematopoietic system   immune system   nervous system   respiratory system	Not classified	Rat	NOAEL 790 mg/kg/day	35 days
Zinc Stearate	Ingestion	heart   endocrine system   gastrointestinal tract   hematopoietic system   liver   immune system   nervous system   eyes   kidney and/or bladder   respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Ethylene	Ingestion	kidney and/or	Some positive	Rat	NOAEL 200	2 years



Glycol		bladder	data exist, but the data are not sufficient for classification		mg/kg/day	
Ethylene Glycol	Ingestion	vascular system	Not classified	Rat	NOAEL 200 mg/kg/day	2 years
Ethylene Glycol	Ingestion	heart   hematopoietic system   liver   immune system   muscles	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
Ethylene Glycol	Ingestion	respiratory system	Not classified	Mouse	NOAEL 12,000 mg/kg/day	2 years
Ethylene Glycol	Ingestion	skin   endocrine system   bone, teeth, nails, and/or hair   nervous system   eyes	Not classified	Multiple animal species	NOAEL 1,000 mg/kg/day	2 years
Iron Oxide (FE2O3)	Inhalation	pulmonary fibrosis   pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Inhalation	endocrine system   hematopoietic system   liver   nervous system	Not classified	Rat	NOAEL 1 mg/l	2 weeks
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 0.005 mg/l	2 weeks
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Inhalation	respiratory system	Not classified	Rat	LOAEL 0.001 mg/l	2 weeks
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Inhalation	heart	Not classified	Rat	NOAEL 0.5 mg/l	2 weeks
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Ingestion	liver   kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 145 mg/kg/day	90 days
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 500 mg/kg/day	2 years
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Ingestion	heart   endocrine system   respiratory system	Not classified	Rat	NOAEL 3,770 mg/kg/day	90 days

### Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Exposure Levels**

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

**Interactive Effects**

Not Determined

## SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

**12.1. Toxicity****Acute aquatic hazard:**

GHS Acute 1: Very toxic to aquatic life.

**Chronic aquatic hazard:**

GHS Chronic 1: Very toxic to aquatic life with long lasting effects.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Benzoyl Peroxide	94-36-0	Green algae	Experimental	72 hours	EC50	0.071 mg/l
Benzoyl Peroxide	94-36-0	Rainbow trout	Experimental	96 hours	LC50	0.06 mg/l
Benzoyl Peroxide	94-36-0	Water flea	Experimental	48 hours	EC50	0.11 mg/l
Benzoyl Peroxide	94-36-0	Green algae	Experimental	72 hours	NOEC	0.02 mg/l
Benzoyl Peroxide	94-36-0	Water flea	Experimental	21 days	EC10	0.001 mg/l
Benzoyl Peroxide	94-36-0	Activated sludge	Experimental	30 minutes	EC50	35 mg/l
Benzoyl Peroxide	94-36-0	Redworm	Experimental	14 days	LC50	>1,000 mg/kg (Dry Weight)
Benzoyl Peroxide	94-36-0	Soil microbes	Experimental	28 days	EC50	2,300 mg/kg (Dry Weight)
Benzoic Acid, C9-11-Branched Alkyl Esters	131298-44-7	Green algae	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
Benzoic Acid, C9-11-Branched Alkyl Esters	131298-44-7	Rainbow trout	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
Benzoic Acid, C9-11-Branched Alkyl Esters	131298-44-7	Water flea	Experimental	48 hours	No tox obs at lmt of water sol	>100 mg/l
Benzoic Acid, C9-11-Branched Alkyl Esters	131298-44-7	Fathead minnow	Experimental	33 days	No tox obs at lmt of water sol	>100 mg/l
Benzoic Acid, C9-11-Branched Alkyl Esters	131298-44-7	Green algae	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
Benzoic Acid, C9-11-Branched Alkyl Esters	131298-44-7	Midge	Experimental	28 days	NOEC	64.7 mg/kg (Dry Weight)
Benzoic Acid, C9-11-Branched Alkyl Esters	131298-44-7	Water flea	Experimental	21 days	No tox obs at lmt of water sol	>100 mg/l
Benzoic Acid, C9-11-Branched Alkyl Esters	131298-44-7	Activated sludge	Experimental	3 hours	EC50	>100 mg/l
Calcium Sulfate	7778-18-9	Activated sludge	Estimated	3 hours	NOEC	1,000 mg/l
Calcium Sulfate	7778-18-9	Algae or other aquatic plants	Experimental	96 hours	EC50	3,200 mg/l
Calcium Sulfate	7778-18-9	Bluegill	Experimental	96 hours	LC50	>2,980 mg/l

**3M™ Cream Hardener (Red, White & Blue)**

Calcium Sulfate	7778-18-9	Water flea	Experimental	48 hours	LC50	>1,970 mg/l
Calcium Sulfate	7778-18-9	Water flea	Estimated	21 days	NOEC	1,270 mg/l
Zinc Stearate	557-05-1	Water flea	Experimental	48 hours	EC50	>100 mg/l
Zinc Stearate	557-05-1	Zebra Fish	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
Ethylene Glycol	107-21-1	Bacteria	Experimental	16 hours	EC50	10,000 mg/l
Ethylene Glycol	107-21-1	Fathead minnow	Experimental	96 hours	LC50	8,050 mg/l
Ethylene Glycol	107-21-1	Green algae	Experimental	72 hours	EC50	>1,000 mg/l
Ethylene Glycol	107-21-1	Water flea	Experimental	48 hours	EC50	>1,100 mg/l
Ethylene Glycol	107-21-1	Green algae	Experimental	72 hours	NOEC	1,000 mg/l
Ethylene Glycol	107-21-1	Water flea	Experimental	21 days	NOEC	100 mg/l
Iron Oxide (FE2O3)	1309-37-1	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	>100 mg/l
Iron Oxide (FE2O3)	1309-37-1	Water flea	Experimental	48 hours	No tox obs at lmt of water sol	>100 mg/l
Iron Oxide (FE2O3)	1309-37-1	Zebra Fish	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
Iron Oxide (FE2O3)	1309-37-1	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	>100 mg/l
Iron Oxide (FE2O3)	1309-37-1	Water flea	Experimental	21 days	No tox obs at lmt of water sol	>100 mg/l
Iron Oxide (FE2O3)	1309-37-1	Activated sludge	Experimental	3 hours	EC50	>10,000 mg/l
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	9038-95-3	Fathead minnow	Experimental	96 hours	LC50	24,500 mg/l
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	9038-95-3	Water flea	Experimental	48 hours	EC50	21,000 mg/l
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	9038-95-3	Activated sludge	Experimental	16 hours	IC50	32,000 mg/l
Ferric Ammonium Ferrocyanide	25869-00-5	Water flea	Endpoint not reached	24 hours	EC50	>100 mg/l
Ferric Ammonium Ferrocyanide	25869-00-5	Activated sludge	Experimental	3 hours	NOEC	100 mg/l
Ferric Ammonium Ferrocyanide	25869-00-5	Common Carp	Experimental	96 hours	LC50	>100 mg/l
Ferric Ammonium Ferrocyanide	25869-00-5	Green algae	Experimental	72 hours	EC50	9.7 mg/l
Ferric Ammonium Ferrocyanide	25869-00-5	Green algae	Experimental	72 hours	NOEC	8 mg/l
Ferric Ammonium Ferrocyanide	25869-00-5	Water flea	Experimental	21 days	EC10	0.168 mg/l
Ferric Ferrocyanide	14038-43-8	Golden Orfe	Estimated	96 hours	LC50	>100 mg/l

**12.2. Persistence and degradability**

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Benzoyl Peroxide	94-36-0	Experimental Biodegradation	28 days	BOD	71 %BOD/ThOD	OECD 301D - Closed bottle test
Benzoyl Peroxide	94-36-0	Experimental Hydrolysis		Hydrolytic half-life	5.2 hours (t 1/2)	OECD 111 Hydrolysis func of pH
Benzoic Acid, C9-11-Branched Alkyl Esters	131298-44-7	Experimental Biodegradation	28 days	BOD	77.7 %BOD/ThOD	OECD 301F - Manometric respirometry
Calcium Sulfate	7778-18-9	Data not available-insufficient	N/A	N/A	N/A	N/A

**3M™ Cream Hardener (Red, White & Blue)**

Zinc Stearate	557-05-1	Experimental Biodegradation	28 days	BOD	14.6 %BOD/ThOD	OECD 301D - Closed bottle test
Ethylene Glycol	107-21-1	Experimental Biodegradation	14 days	BOD	90 %BOD/ThOD	OECD 301C - MITI test (I)
Iron Oxide (Fe <sub>2</sub> O <sub>3</sub> )	1309-37-1	Data not available-insufficient	N/A	N/A	N/A	N/A
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	9038-95-3	Experimental Biodegradation	28 days	CO <sub>2</sub> evolution	45 %CO <sub>2</sub> evolution/THCO <sub>2</sub> evolution (does not pass 10-day window)	similar to OECD 301B
Ferric Ammonium Ferrocyanide	25869-00-5	Data not available-insufficient	N/A	N/A	N/A	N/A
Ferric Ferrocyanide	14038-43-8	Data not available-insufficient	N/A	N/A	N/A	N/A

**12.3 : Bioaccumulative potential**

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Benzoyl Peroxide	94-36-0	Experimental Bioconcentration		Log Kow	3.2	OECD 117 log Kow HPLC method
Benzoic Acid, C9-11-Branched Alkyl Esters	131298-44-7	Modeled Bioconcentration		Bioaccumulation factor	288	Catalogic™
Benzoic Acid, C9-11-Branched Alkyl Esters	131298-44-7	Experimental Bioconcentration		Log Kow	4.61	EC A.8 Partition Coefficient
Calcium Sulfate	7778-18-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Zinc Stearate	557-05-1	Experimental Bioconcentration		Log Kow	4.64	OECD 117 log Kow HPLC method
Ethylene Glycol	107-21-1	Experimental Bioconcentration		Log Kow	-1.36	
Iron Oxide (Fe <sub>2</sub> O <sub>3</sub> )	1309-37-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	9038-95-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Ferric Ammonium Ferrocyanide	25869-00-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Ferric Ferrocyanide	14038-43-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

**12.4. Mobility in soil**

Please contact manufacturer for more details

**12.5 Other adverse effects**

No information available.

**SECTION 13: Disposal considerations****13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a

permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes.

## **SECTION 14: Transport Information**

### **Australian Dangerous Goods Code (ADG) - Road/Rail Transport**

**UN No.:** UN3108

**Proper shipping name:** ORGANIC PEROXIDE TYPE E, SOLID , ( Dibenzoyl Peroxide (as a paste), <= 52% )

**Class/Division:** 5.2

**Sub Risk:** Not applicable.

**Packing Group:** Not applicable.

**Special Instructions:** Limited quantity may apply

**Hazchem Code:** 1W

**IERG:** 32

### **International Air Transport Association (IATA) - Air Transport**

**UN No.:** UN3108

**Proper shipping name:** ORGANIC PEROXIDE TYPE E, SOLID , ( Dibenzoyl Peroxide (as a paste), <= 52% )

**Class/Division:** 5.2

**Sub Risk:** Not applicable.

**Packing Group:** Not applicable.

### **International Maritime Dangerous Goods Code (IMDG)- Marine Transport**

**UN No.:** UN3108

**Proper shipping name:** ORGANIC PEROXIDE TYPE E, SOLID , ( Dibenzoyl Peroxide (as a paste), <= 52% )

**Class/Division:** 5.2

**Sub Risk:** Not applicable.

**Packing Group:** Not applicable.

**Marine Pollutant:** Not applicable.

**Special Instructions:** Limited quantity may apply

## **SECTION 15: Regulatory information**

### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

#### **Australian Inventory Status:**

All components of this product are listed on or exempt from the Australian Inventory of Industrial Chemicals (AIIC). Conditions may apply prior to introduction for direct importers of this product, Please contact 3M Australia on 136 136 for further details.

**Poison Schedule:** This product is intended for Industrial or Professional Use only and therefore is not packaged and labelled in accordance with the requirements of the Standard for the Uniform Scheduling of Medicines and Poisons.

## **SECTION 16: Other information**

### **Revision information:**

Complete document review.

**DISCLAIMER:** The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

**3M Australia SDSs are available at [www.3m.com.au](http://www.3m.com.au)**